

SPECIFICATIONS	30-8 IRON EAGLE	MODEL T40-14	MODEL 45-14	55 IRON EAGLE	MODEL 56-14	PRO 56	MODELS 66-24
Throat Depth	4 1/2"	5 1/4"	6"	7 3/4"	6"	6"	9"
Punch	3/4" hole in 1/2" 1 1/4" hole in 5/16"	1" hole in 1/2" 1 3/8" hole in 3/8"	1 1/8" hole in 1/2" 1 1/2" hole in 3/8"	1 3/8" hole in 1/2" 7/8" hole in 3/4"	1 1/4" hole in 1/2" 15/16" hole in 3/4"	1 1/4" hole in 1/2" 13/16" hole in 3/4"	1 5/8" hole in 1/2" 2 1/4" hole in 3/8"
Bar Shear	1/4" X 8" 1/2" X 6"	3/8" x 14" 1/2" x 10" 5/8" x 6"	3/8" x 14" 1/2" x 10" 5/8" x 6"	1/2" X 14" 3/4" X 4"	3/8" x 14" 1/2" x 10" 5/8" x 8" 3/4" x 6"	3/8" x 14" 1/2" x 10" 5/8" x 8" 3/4" x 6"	1/4" x 24" 3/8" x 22" 1/2" x 16" 3/4" x 10" 1" x 6"
Angle Shear 90° - Slug Type		3" x 3" x 3/8"	3" x 3" x 3/8"		3" x 3" x 3/8"	3" x 3" x 3/8"	6" x 6" x 3/8"
- Server Cut	3" X 3" X 1/4"	3" x 3" x 1/4"	3" x 3" x 1/4"	4" X 4" X 3/8"	4" x 4" x 3/8"	4" x 4" x 3/8"	5" x 5" x 1/2" 4" x 4" x 3/8"
Miter Angle 45° - Bar Shear - Slug Type	2" X 2" standard	3" x 3" x 3/8" 2" x 2" x 5/16"	3" x 3" x 3/8" 2" x 2" x 5/16"		3" x 3" x 3/8" 2" x 2" x 5/16"	3" x 3" x 3/8" 2" x 2" x 5/16"	4" x 4" x 1/2" 4" x 4" x 3/8"
Channel Shear	1" X 2" standard	1" & 2" combined or 3" standard	1" & 2" combined or 3" standard	1" X 2" combined or 3" standard	2" & 3" combined 4" standard	2" & 3" combined 4" standard	2" & 3" combined 4" or 5" standard
Rod Shear - Round (max) - Square (max)	5/8" 5/8"	3/4" 3/4"	3/4" 3/4"	1" 1"	1 1/16" 1 1/16"	1 1/16" 1 1/16"	1 1/4" 1 1/4"
Coper Notcher 90°	For 3" X 3" X 1/4" angle	For 3" x 3" x 1/4" angle	For 3" x 3" x 1/4" angle	For 3" X 3" X 1/4" angle	For 3" x 3" x 1/4" angle	For 3" x 3" x 1/4" angle	For 4" x 4" x 3/8" angle
Square Notcher	N/A	1 3/4" x 2" x 1/4"	1 3/4" x 2" x 1/4"		1 3/4" x 2" x 1/4"	1 3/4" x 2" x 1/4"	3" x 3" x 3/8"
Notching Station Square Notcher		--	--		--	2" x 3" x 3/8"	--
Pipe Notcher Sched 40 or 80	1/2", 3/4", 1", 1 1/4", 1 1/2", 1 3/4", 2"	1/2", 3/4", 1", 1 1/4", 1 1/2"	1/2", 3/4", 1", 1 1/4", 1 1/2"	1/2", 3/4", 1", 1 1/4", 1 1/2", 1 3/4", 2"	1/2", 3/4", 1", 1 1/4", 1 1/2", 2"	1/2", 3/4", 1", 1 1/4", 1 1/2", 2"	1/2", 3/4", 1", 1 1/4", 1 1/2", 2"
Brake	6" x 1/4"	6" or 9" x 1/4"	6" or 9" x 1/4"	10" x 1/4"	6" or 9" x 1/4"	6" or 9" x 1/4"	6", 9", 14", 18" or 24"
Strokes per minute - light material - at max capacity	9	50 7	50 7	8	50 7	50 7	50 9
Hydraulics	1,000 psi	1,000 psi	1,000 psi	2,300 psi	1,200 psi	1,200 psi	2,000 psi
Oil Capacity	15 quarts	15 quarts	15 quarts	20 quarts	20 quarts	20 quarts	16 gallons
Motor - Standard - Optional	3 HP, 1 or 3 phase	3 HP, 3 phase 3 HP, 1 phase	3 HP, 3 phase 3 HP, 1 phase	5 HP, 1 or 3 phase	5 HP, 3 phase 5 HP, 1 phase	5 HP, 3 phase 5 HP, 1 phase	7 1/2 HP, 3 phase 7 1/2 HP, 1 phase
Dimensions - Width - Length - Height - Bar shear work ht. - Punch table top ht. - Cavity table top ht. - Notcher station working ht.	24" 27" 50"	32" 46" 63 1/2" 30" 38 3/16" 37 1/4" --	28" 34" 60" 29" 38 1/4" 37 1/4" --	38" 43" 58"	27 1/4" 33" 57" 29" 38 1/4" 37 1/4" --	27 1/4" 33" 57" 29" 38 1/4" 37 1/4" 26"	37" 46" 70" 29" 29" 39 1/4" 41"
Weight (net)	880 lbs.	1,710 lbs.	1,240 lbs.	1,500 lbs.	1,330 lbs	1,720 lbs.	2,840 lbs.